

[Wireless LAN] : Enable
Link Status : Active
MAC Address : 00:1E:8F:8E:58:34

SSID : SuperNet
Connection Mode : Infrastructure
Channel : 10
Encryption : AES
WEP Key Length : Inactive
Authentication : WPA2-PSK
Signal Strength : 72[%]

TCP/IP Version : IPv4
IP Address : 192.168.1.67
Default Gateway : 192.168.1.254
Subnet Mask : 255.255.255.0
Subnet Prefix Length :

IPsec :
Security Protocol :

[Wired LAN] : Disable
Link Status : Inactive
MAC Address : 00:1E:8F:88:8E:8F

TCP/IP Version : IPv4
IP Address :
Default Gateway :
Subnet Mask :
Subnet Prefix Length :

IPsec :
Security Protocol :


[Other Settings]

Printer Name : Canon-MX350-A
Shared Memory Card : Enable

WSD : Enable
WSD Timeout : 1[min]
LLTD : Enable
LPR Protocol : Enable

Bonjour : Enable
Bonjour Service Name : Canon MX350 series _8E5834888E8F
Bonjour LPR Service : Disable

Printer Test Page



Media Limits: 0.00 x 0.00 to 8.50 x 11.00 inches

Job ID: Canon_MX350-35

Driver: STP01918.PPD

Driver Version: 5.2.9

Description: Canon Multi Function

Driver Version: Canon Multi Function

Make and Model: Canon PIXMA MX350 - CUPS+Gutenprint v5.2.9 Simplified

Printer: Canon_MX350

Created at: Mon Feb 10 09:07:48 2014

Printed at: Mon Feb 10 09:07:48 2014